

LED Deckenleuchte DLP 7410 – DLP 7540

Multipower Steuerung per DIP-Schalter

- Lichtstrom über DIP-Schalter in 16 Stufen (4-16W), 13 Stufen (9,5-28W, 11,5-35W, 11 Stufen (30,5-52W) einstellbar
- optionale Erweiterungen:
 - 1-10V dimmbar
 - PME Bewegungsmelder auf Anfrage
 - Notlicht nachrüstbar

4-16 W	Ø 300 mm	3000K	450 – 1700lm	FL-DLP7510.1783M
4-16 W	Ø 300 mm	4000K	450 – 1700lm	FL-DLP7510.1784M
9.5-28 W	Ø 375 mm	3000K	1100 – 3300lm	FL-DLP7520.3383M
9.5-28 W	Ø 375 mm	4000K	1100 – 3300lm	FL-DLP7520.3384M
11.5-35 W	Ø 480 mm	3000K	1850 – 5500lm	FL-DLP7530.5583M
11.5-35 W	Ø 480 mm	4000K	1850 – 5500lm	FL-DLP7530.5584M
30.5-52 W	Ø 480 mm	3000K	4100 – 7000lm	FL-DLP7530.7083M
30.5-52 W	Ø 480 mm	4000K	4100 – 7000lm	FL-DLP7530.7084M
11.5-35 W	Ø 600 mm	3000K	1850 – 5500lm	FL-DLP7540.5583M
11.5-35 W	Ø 600 mm	4000K	1850 – 5500lm	FL-DLP7540.5584M
30.5-52 W	Ø 600 mm	3000K	4100 – 7000lm	FL-DLP7540.7083M
30.5-52 W	Ø 600 mm	4000K	4100 – 7000lm	FL-DLP7540.7084M

DALI steuerbar

- DALI steuerbar
- optionale Erweiterungen:

16 W	DALI	Ø 300 mm	3000K	1700lm	FL-DLP7510.1783DA
16 W	DALI	Ø 300 mm	4000K	1700lm	FL-DLP7510.1784DA
28 W	DALI	Ø 375 mm	3000K	3300lm	FL-DLP7520.3383DA
28 W	DALI	Ø 375 mm	4000K	3300lm	FL-DLP7520.3384DA
35 W	DALI	Ø 480 mm	3000K	5500lm	FL-DLP7530.5583DA
35 W	DALI	Ø 480 mm	4000K	5500lm	FL-DLP7530.5584DA
52 W	DALI	Ø 480 mm	3000K	7000lm	FL-DLP7530.7083DA
52 W	DALI	Ø 480 mm	4000K	7000lm	FL-DLP7530.7084DA
35 W	DALI	Ø 600 mm	3000K	5500lm	FL-DLP7540.5583DA
35 W	DALI	Ø 600 mm	4000K	5500lm	FL-DLP7540.5584DA
52 W	DALI	Ø 600 mm	3000K	7000lm	FL-DLP7540.7083DA
52 W	DALI	Ø 600 mm	4000K	7000lm	FL-DLP7540.7084DA

optionales Zubehör

Seilabhängung	FL-SA75-V3
---------------	------------

Ø x H	30 x 10,5 cm
	37,5 x 12,5 cm
	48 x 15 cm
	60 x 16,5 cm

Farbe	weiß
Material	Gehäuse Stahl / Abdeckung Kunststoff, opal
Lieferumfang	Betriebsgerät
inklusive	